(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 16 June 2005 (16.06.2005)

PCT

(10) International Publication Number WO 2005/054956 A2

(51) International Patent Classification⁷: G02B 13/14

G03F 7/20,

(21) International Application Number:

PCT/EP2004/013519

(22) International Filing Date:

25 November 2004 (25.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/526,096

2 December 2003 (02.12.2003) U

- (71) Applicant (for all designated States except US): CARL ZEISS SMT AG [DE/DE]; Carl-Zeiss-Strasse 22, 73447 Oberkochen (DE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ROSTALSKI, Hans-Jürgen [DE/DE]; Dietrich Bonhoeffer Strasse 9, 73447 Oberkochen (DE). DODOC, Aurelian [RO/DE]; Hainbuchenweg 7, 73447 Oberkochen (DE). ULRICH, Wilhelm [DE/DE]; Lederackerring 44, 73434 Aalen (DE). EPPLE, Alexander [DE/DE]; Langertstrasse 38, 73431 Aalen (DE).


- (74) Agents: SCHORR, Frank et al.; Augustenstrasse 46, 80333 München (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: PROJECTION OPTICAL SYSTEM



(57) Abstract: A projection optical system comprises a plurality of lenses disposed along an optical axis of the projection optical system; wherein the plurality of lenses is dividable into four non-overlapping groups of lenses of positive and negative refractive powers, wherein the following relation (1) is fulfilled: (1) wherein: y is half a diameter in mm of a maximum image field imaged by the projection optical system, NA is a maximum numerical aperture on a side of the second object, ϕ_i is a refractive power in mm⁻¹ of the ith lens, k is a total number of lenses of the projection optical system, and wherein V_1 is greater than 0.045.

WO 2005/054956 A2



Published:

 without international search report and to be republished upon receipt of that report For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.